

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

DIN rail diode module 48 V DC/2x20 A or 1x40 A. Uniform redundancy up to the consumer.



Product Description

A safe redundant system is the result of the parallel connection of two power supply units which are decoupled from one another. To further increase system availability, QUINT DIODE provides the solution: decoupling with diode.

Your advantages

- Flexible
- Rugged design
- Consistent redundancy up to the load

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

Commercial Data

Item number	2907720
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	CMR
Product Key	CMRI44
Catalog Page	Page 307 (C-4-2019)
GTIN	4055626231396
Weight per Piece (including packing)	879 g
Weight per Piece (excluding packing)	879 g
Customs tariff number	85049090
Country of origin	CN

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

Technical Data

Input data

DC operation

Nominal input voltage range	48 V DC
Input voltage range	30 V DC ... 56 V DC
Voltage type of supply voltage	DC
Reverse polarity protection	< yes120 V
Nominal input current (I_N)	2x 20 A (-40 °C ... 60 °C)
	1x 40 A (-40 °C ... 60 °C)
Maximum current I_{max}	2x 30 A (-40 °C ... 40 °C)
	1x 60 A (-40 °C ... 40 °C)
Input current I_{Static}	2x 25 A (40 °C)
Input current $I_{Dynamic}$	2x 30 A (5 s)
Input current I_{SFB}	2x 120 A (15 ms)
Nominal input current (I_N)	2x 20 A (-25 °C ... 60 °C)
	1x 40 A (-25 °C ... 60 °C)
Maximum current I_{max}	2x 30 A (-25°C ... 40°C)
	1x 60 A (-25°C ... 40°C)
Transient surge protection	Varistor
Voltage drop, input/output	0.7 V
Input voltage range DC	30 V DC ... 56 V DC

Output data

Efficiency	> 97 %
Nominal output voltage	48 V DC
Output voltage	$U_{in} -$
Nominal output current (I_N)	40 A (Increasing power)
	20 A (Redundancy)
Derating	60 °C ... 70 °C (2.5%/K)
Power loss nominal load max.	14 W ($I_{OUT} = 20 A$)
Connection in series	No
Derating	60 °C ... 70 °C 2.5 %/K

Connection data

Input

Connection method	Screw connection
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section flexible min.	0.5 mm ²
Conductor cross section flexible max.	16 mm ²
Conductor cross section AWG min.	10

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

Conductor cross section AWG max.	6
Stripping length	10 mm
Screw thread	M4
Tightening torque, min	1.2 Nm
Tightening torque max	1.5 Nm

Output

Connection method	Screw connection
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section flexible min.	0.5 mm ²
Conductor cross section flexible max.	16 mm ²
Conductor cross section AWG min.	10
Conductor cross section AWG max.	6
Stripping length	10 mm
Screw thread	M4
Tightening torque, min	1.2 Nm
Tightening torque max	1.5 Nm

Electrical properties

Insulation voltage input, output / housing	1000 V
--	--------

Product properties

Product type	Redundancy module
MTBF (IEC 61709, SN 29500)	40000000 h (40 °C)

Insulation characteristics

Protection class	III
Degree of pollution	2

Dimensions

Width	50 mm
Height	130 mm
Depth	125 mm

Installation dimensions

Installation distance right/left	5 mm / 5 mm
Installation distance top/bottom	50 mm / 50 mm

Mounting

Mounting type	DIN rail mounting
Assembly instructions	alignable: P _N ≥50%, 5 mm horizontally, 15 mm next to active components, 50 mm vertically alignable: P _N <50%, 0 mm horizontally, 40 mm vertically top, 20 mm vertically bottom
Mounting position	horizontal DIN rail NS 35, EN 60715

Redundancy module - QUINT4-DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

Material specifications

Inflammability class in acc. with UL 94 (housing / terminal blocks)	V0
Housing material	Metal
Housing material	Aluminum / stainless steel

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 70 °C (> 60 °C Derating: 2,5 %/K)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Maximum altitude	≤ 5000 m
Climatic class	3K3 (in acc. with EN 60721)
Max. permissible relative humidity (operation)	≤ 95 % (at 25 °C, non-condensing)
Shock	18 ms, 30g, in each space direction (according to IEC 60068-2-27)
Vibration (operation)	< 15 Hz, amplitude ±2.5 mm (according to IEC 60068-2-6) 15 Hz ... 150 Hz, 2.3g, 90 min.

Standards and regulations

Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
Standard – Protection against shock currents, basic requirements for protective separation in electrical equipment	EN 50178
Standard – Safety extra-low voltage	IEC 60950-1 (SELV) and EN 60204-1 (PELV)
Standard - Safe isolation	DIN VDE 0100-410

Approval data

UL approvals	UL/C-UL listed UL 508
	UL/C-UL Recognized UL 60950-1
	UL ANSI/ISA-12.12.01 Class I, Division 2, Groups A, B, C, D (Hazardous Location)

Conformity/Approvals

ATEX	□ II 3 G Ex ec IIC T4 Gc
	DEKRA 20ATEX0041 X
IECEX	Ex ec IIC T4 Gc
	IECEX DEK 20.0022X

EMC data

Low Voltage Directive	Conformance with Low Voltage Directive 2014/35/EC
Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
EMC requirements for noise emission	EN 61000-6-3
	EN 61000-6-4
EMC requirements for noise immunity	EN 61000-6-1

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

EN 61000-6-2

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40




2907720

<https://www.phoenixcontact.com/in/products/2907720>

Drawings

Block diagram



Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

Approvals



cUL Recognized
Approval ID: FILE E 211944



UL Recognized
Approval ID: FILE E 211944



EAC
Approval ID: RU S-DE.BL08.W.00764



DNV GL
Approval ID: TAA000011F



UL Listed
Approval ID: FILE E 123528



cUL Listed
Approval ID: FILE E 123528



ATEX
Approval ID: DEKRA 20ATEX0041X



EAC Ex
Approval ID: RU C-DE.HB49.B.00004



IECEx
Approval ID: IECEx DEK 20.0022X



CCC
Approval ID: 2020322303003426



NEPSI
Approval ID: GYJ20.1591X



cUL Listed
Approval ID: FILE E 199827

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>



UL Listed

Approval ID: FILE E 199827

INMETRO

Approval ID: DNV 19.0186X

cULus Recognized

cULus Listed

cULus Listed

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

Classifications

ECLASS

ECLASS-9.0	27371010
ECLASS-10.0.1	27371010
ECLASS-11.0	27371010

ETIM

ETIM 8.0	EC000683
----------	----------

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25; For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Redundancy module - QUINT4- DIODE/48DC/2X20/1X40



2907720

<https://www.phoenixcontact.com/in/products/2907720>

Accessories

Mounting adapter

Mounting adapter - UWA 182/52 - 2938235

<https://www.phoenixcontact.com/in/products/2938235>



Universal wall adapter for securely mounting the device in the event of strong vibrations. The device is screwed directly onto the mounting surface. The universal wall adapter is attached on the top/bottom.

Mounting adapter

Mounting adapter - QUINT-PS-ADAPTERS7/1 - 2938196

<https://www.phoenixcontact.com/in/products/2938196>

Assembly adapter for QUINT-PS... power supply on S7-300 rail



Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in